

DATASHEET

SKYSAFE PRO+



GENERAL

Art.Nr:	L-0848-1C8	Standards:	EN 354:2010, EN 355:2002, EN 795:2012/B, RFU PPE-R/11.074
GTIN:	4030281311157	Net weight:	2.44 kg
E-class number:	40-02-01-04	Gross weight:	2.44 kg
Customs tariff number:	56090000		

DATASHEET

SKYSAFE PRO+

The SKYSAFE PRO+ is a state-of-the-art lanyard for working at height and impresses with maximum safety, efficiency and flexibility. Its particularly compact energy absorber allows unrestricted freedom of movement - even in confined structures - and thus ensures trouble-free working.

The integrated energy absorbers reliably reduce the fall arrest forces to less than 6 kN in the event of a fall, even with a user weight of between 50 and 150 kg. The system also offers so-called short-circuit safety, which significantly minimizes the risk of misuse. Use on sharp edges with a radius of more than 0.5 mm is also possible without any problems.

An integrated drop indicator enables a quick visual check of readiness for use. The overall length of 1.80 m ensures a high level of comfort and maximum mobility. Thanks to a wide range of carabiner options, the SKYSAFE PRO+ can be flexibly adapted to different operating conditions.

Certified in accordance with EN 354, EN 355, EN 795/B and RFU 11.074, the lanyard meets the highest quality and safety requirements.

FEATURES

Colour:	Black, Orange
Fall indicator:	Yes
Impact force:	6.00 kN
Hand wash:	40 °C
Edge approved:	Yes
Maximum lifetime:	10 years
Minimum tensile strength:	22.00 kN
Minimum temperature:	-35 °C
Maximum temperature:	45 °C
Rescue loop:	Yes
Lanyard type:	Y-Version
Connector:	FS92

DIMENSIONS

Rope length:	1.80 m
length_lanyard:	1.80 m
Lanyard rope diameter:	30.00 mm

MATERIAL

Material:	Polyamide, Polyester, Steel
-----------	-----------------------------