

Data sheet

SIRIUS



GENERAL

Art. no.:	A-050
EAN:	4030281286943
Standard:	DIN EN 12841-C:2006 DIN EN 341-2A:2011

E-class number:	40-02-01-06
Customs no.:	84798997

Data sheet

SIRIUS

SIRIUS packs the advantages of the best descenders for industrial and rescue applications into an extremely compact design - for better handling and long service life. SIRIUS lies perfectly in your hand. The auto-returning operating lever has a particularly small radius of motion so that you can work fast, accurately, more comfortably and safely. During rope insertion, which is intuitive and simple, the carabiner on the harness can stay connected to the device. We designed the route of the rope in such a way that it is protected from twisting and kinking, and from excessive wear and tear.

SIRIUS was developed for extended use under the toughest of conditions. That's why it is made of up to 100 % metal - without any vulnerable synthetic spots.

SIRIUS. Best ergonomics and long service life in its most compact form:

- Outstanding handling thanks to compact design and intuitive route of the rope
- Long-lasting and sturdy: 100% metal
- Auto-locking function, improved an

GENERAL

Internat. standard:	ANSI Z359.4:2013
---------------------	------------------

FEATURES

Abseiling speed:	2,00 m/s
Max. number of persons:	2
Rated load:	250 KG
Temperature:	from 60 °C to -30 °C

DIMENSIONS

Size:	47x79x175mm
Weight:	0,51 kg

MATERIAL

Material:	Aluminium, Steel
-----------	------------------
