


| Universe    | Professional              |
|-------------|---------------------------|
| Туре        | Verticality               |
| Category    | Anchors                   |
| Subcategory | Rock and concrete anchors |



## COEUR PULSE 12 mm

The COEUR PULSE 12 mm is a removable, high-quality stainless steel anchor that can be installed and removed for reuse very simply and rapidly without tools. The locking function limits the risk of accidental removal. The COEUR hanger can rotate once installed and when laterally loaded during use, allowing it to better align with the systems in place.



The anchor can be installed and removed for reuse very simply and rapidly, without tools.



Manual screw-lock function limits the risk of involuntary removal.



The COEUR hanger has a large opening, making it easy to clip and allowing two carabiners to be installed simultaneously.



The COEUR hanger can rotate once installed and when laterally loaded during use, allowing it to better align with the systems in place.



| Short Description | Removable anchor with locking function   |
|-------------------|--|
| Selling Points    | <ul> <li>Easy to use:</li> <li>Quick and simple to install and remove without tools, so it can be reused</li> <li>Locking function limits the risk of accidental removal</li> <li>The locking knob is easy to handle, even with gloves</li> <li>Easy to clip:</li> <li>Wide, ergonomic hanger opening makes it easier to clip a carabiner</li> <li>Hanger opening is wide enough to accommodate two carabiners at the same time</li> <li>Thickness and rounded edges of the COEUR hanger help reduce wear on carabiners</li> <li>Hanger rotation:</li> <li>COEUR hanger can rotate once installed and when laterally loaded during use, so it aligns with the pull of the connector</li> </ul> |
| Specification     | <ul> <li>Material(s): Stainless steel, plastic</li> <li>Certification(s): CE EN 795 B, CE EN 959, TS 16415, UKCA</li> </ul>  |

## Specifications by reference

| Reference(s)                            | G037BA00      |
|---|---------------|
| Diameter                                | 12 mm         |
| Weight                                  | 140 g         |
| Drilling depth                          | 6,5 cm        |
| Drilling diameter                       | 12 mm         |
| Shear strength in 50 MPa concrete       | > 25 kN       |
| Pull-out strength in<br>concrete 50 MPa | > 20 kN       |
| Shear strength in 25 MPa concrete       | 25 kN         |
| Pull-out strength in<br>concrete 25 MPa | 20 kN         |
| Made in                                 | FR            |
| Guarantee                               | 3 years       |
| Inner Pack Count                        | 1             |
| Quantity Per Box                        | 8             |
| EAN                                     | 3342540842243 |

## Spare part(s)

COEUR STAINLESS

Related product(s)

OK WILLIAM Am'D OXAN VULCAN Bm'D

