

Universe	Professional
Type	Verticality
Category	Anchors
Subcategory	Anchor straps for tree care



TREESBEE

The TREESBEE anchor strap is used to improve rope glide at the anchor while protecting the tree from abrasion. It is designed for ropes with spliced terminations (the splice goes through the small ring). The galvanized steel rings provide great durability.



Galvanized steel ring for greater durability.

Short Description Friction saver for tree care, designed for ropes with spliced terminations



Selling Points

- Friction saver designed to facilitate movement within the tree:
 - Protects the tree and improves rope glide at the anchor
 - Possible to install and retrieve from the ground
 - Wide, rigid webbing limits twisting
 - Strap with large and small diameter rings for ropes with spliced terminations (the splice goes through the small ring)
 - Triple thickness of termination on large ring side makes the webbing more rigid for retrieval
 - Two-person use is possible when performing a rescue
- Galvanized steel ring for greater durability:
 - Large ring diameter (interior/exterior): 46/70 mm
 - Small ring diameter (interior/exterior): 28/52 mm
- Compatible with 30 mm retrieval ball
- Available in two sizes: 90 and 110 cm

Specification

- Material(s): Steel, nylon
- Breaking strength: 23kN
- Max. rope diameter: 13mm
- Certification(s): CE EN 795 B, TS 16415, EAC

Specifications by reference

Reference(s)	G040AA00	G040AA01
		
Length	90 cm	110 cm
Weight	420 g	440 g
Made in	TW	TW
Guarantee	3 years	3 years
Inner Pack Count	1	
Quantity Per Box	20	20
EAN	3342540839601	3342540840010

Related product(s)

FLOW 11.6 mm
CONTROL 12.5 mm
EJECT
ZIGZAG®
ZIGZAG® PLUS
SEQUOIA®
SEQUOIA® SRT