

Universe	Professional
Type	Verticality
Category	Ropes
Subcategory	Low stretch kernmantel ropes




VECTOR 12.5 mm


The VECTOR 12.5 mm low stretch kernmantel rope is designed for rescue. The large diameter ensures great strength and excellent grip when handling heavy loads. The EverFlex technology guarantees great flexibility and consistent performance over time. Rope available in six colors and four lengths.



The large diameter ensures great strength and excellent grip when handling heavy loads.



EverFlex technology ensures great flexibility over time and under any conditions (water, dust, mud...), allowing it to maintain consistent handling and optimal performance with devices.



It is possible to order a rope of a specified length.

Short Description Low stretch kernmantel, high-strength rope with excellent handling, for rescue





Selling Points





- Large diameter, ensuring great strength and excellent handling when manipulating heavy loads
- Consistent performance over time:
 - construction with nylon core and polyester sheath, with specific weave
 - EverFlex technology ensures great flexibility over time and under any conditions (water, dust, mud...), allowing it to maintain excellent handling and optimal performance with devices
- Available in six colors for easier identification of different kits: white, yellow, black, blue, red and orange
- Standard lengths: 50, 100, 200 and 500 m
- Customization on request:
 - option of ordering a rope of a specified length (up to 700 m)
 - addition of sewn terminations manufactured on one or both ends, providing a ready-to-use rope. These terminations have a protective sheath that keeps the connector in position and facilitates handling. They are also stronger than a figure-eight knot





Specification





- Diameter: 12,5mm
- Material(s): polyester, nylon
- Certification(s): CE EN 1891 type A, UKCA, EAC, NFPA 1983 General Use
- Weight per meter: 111g
- Strength tied with figure-eight knot: 23kN
- Strength with sewn termination: 34kN
- Impact force (factor 0,3): 5,7kN
- Number of factor 1 falls: 15
- Construction: 32 carrier
- Percentage of sheath: 46%
- Static elongation: 2,8%




Specifications by reference

Reference(s)	R078AA03	R078AA04	R078AA05	R078AA38
				
Length	50 m	50 m	50 m	50 m
Color(s)	white	yellow	black	blue
Made in	CZ	CZ	CZ	CZ
Guarantee	3 years	3 years	3 years	3 years
Inner Pack Count	1	1	1	1
Quantity Per Box	1	1	1	1
EAN	3342540816732	3342540816749	3342540816756	3342540822733

Reference(s)	R078AA39	R078AA40	R078AA09	R078AA10
				
Length	50 m	50 m	100 m	100 m
Color(s)	red	orange	white	yellow
Made in	CZ	CZ	CZ	CZ
Guarantee	3 years	3 years	3 years	3 years
Inner Pack Count	1	1	1	1
Quantity Per Box	1	1	1	1
EAN	3342540822948	3342540822955	3342540816794	3342540816800

Reference(s)	R078AA11	R078AA12	R078AA13	R078AA14
				
Length	100 m	100 m	100 m	100 m
Color(s)	black	blue	red	orange
Made in	CZ	CZ	CZ	CZ
Guarantee	3 years	3 years	3 years	3 years
Inner Pack Count	1	1	1	1
Quantity Per Box	1	1	1	1
EAN	3342540816817	3342540816824	3342540816831	3342540816848

Reference(s)	R078AA21	R078AA22	R078AA23	R078AA24
				
Length	200 m	200 m	200 m	200 m
Color(s)	white	yellow	black	blue
Made in	CZ	CZ	CZ	CZ
Guarantee	3 years	3 years	3 years	3 years
Inner Pack Count	1	1	1	1
Quantity Per Box	1	1	1	1
EAN	3342540816916	3342540816923	3342540816930	3342540816947

Reference(s)	R078AA25	R078AA26	R078AA28
			
Length	200 m	200 m	500 m

Color(s)	red	orange	white
Made in	CZ	CZ	CZ
Guarantee	3 years	3 years	3 years
Inner Pack Count	1	1	1
Quantity Per Box	1	1	1
EAN	3342540816954	3342540816961	3342540816985

Accessory(ies)	PROTEC SET CATERPILLAR ROLL MODULE
-----------------------	--

Related product(s)	I'D® L ASAP®
---------------------------	-----------------