

DATASHEET ACTSAFE ICX POWER ASCENDER



GENERAL

Art.Nr:	POA-030-1-EU	Net weight:	7.40 kg
GTIN:	4030281309840	Gross weight:	7.40 kg
Customs tariff number:	84253100		

www.skylotec.com | Datenblatt, 19.10.23



DATASHEET

ACTSAFE ICX POWER ASCENDER

The ICX battery-powered hoist is a motorised system to ensure the transport of persons or loads to areas that are difficult to access and where occasional or

recurring work is carried out. The ICX POWER ASCENDER considerably simplifies and accelerates work on complex structures and makes expensive access systems or lifting platforms superfluous. ICX forms a

highly flexible system for easy

and cost-efficient cleaning or maintenance. In an emergency, the ICX can be controlled by remote control. The operation and use of the ICX can be learned in special training courses.

- Simplifies and accelerates work on structures that are difficult to access - Gentle application

- Control by remote control up to 50 m

FEATURES

Battery range at 20° C & 100 kg load:	230	
Application areas:	Various	
Energy source:	Removeable Battery	
Colour:	polyethylene_terephth alate	
Underwater operations:	No	
Water dust resistance:	IP 55	
Charging time:	80 minutes	
Maximum descent speed:	24 m/min	
Max. ascent rate:	24 m/min	
Maximum compatible rope diameter:	11.00 mm	
Maximum temperature:	40 °C	
Minimum descent speed:	1 m/min	
Min. ascent rate:	1 m/min	
Minimum compatible rope diameter:	11.00 mm	
Minimum temperature:	-10 °C	
Emergency descent function:	Yes	
Emergency stop function:	Yes	
Remote control range:	50 m	
DIMENSIONS		

Working load limit:

MATERIAL

185.00 kg



DATASHEET ACTSAFE ICX POWER ASCENDER

Material:

Steel, Aluminium, Nylon