

Univers	Professional
Type	Products
Category	Pulleys and Progress-Capture Pulleys
Subcategory	Prusik-Minding Pulleys



## MINDER S1

The MINDER S1 pulley is designed for work-at-height professionals and for setting up on-site rescue systems. Its special side plates are designed for use with a Prusik friction hitch in progress-capture systems. Compact and lightweight, it provides good efficiency for handling moderate loads.

---

Short Description	Lightweight, high efficiency Prusik pulley
-------------------	--------------------------------------------

---

Selling Points	<ul style="list-style-type: none"><li>• Use in progress-capture systems:<ul style="list-style-type: none"><li>- Moving side plates designed for use with a Prusik friction hitch</li></ul></li><li>• Designed for handling moderate loads:<ul style="list-style-type: none"><li>- Sheave mounted on sealed ball bearings provides high efficiency</li><li>- Lightweight and compact, ideal for everyday work-at-height use or for on-site rescue</li><li>- Large attachment holes fit up to two carabiners for ease of use</li></ul></li><li>- Specific side plate design protects the rope path</li><li>- Attachment holes allow most European-standard carabiners to rotate</li></ul>
----------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

---

Specification	<ul style="list-style-type: none"><li>• Rope compatibility: 6 to 11 mm</li><li>• Sheave diameter: 25mm</li><li>• Ball bearings: Yes</li><li>• Efficiency: 91%</li><li>• Maximum working load: 5kN</li><li>• Breaking strength: 23kN</li><li>• Weight: 71g</li><li>• Certification(s): CE EN 12278, UIAA, NFPA Technical Use, XF 494 Light</li><li>• Material(s): Aluminum, stainless steel</li></ul>
---------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

---

Specifications by reference

Reference(s)	P060AA00
Color(s)	Yellow
Made in	FR
Guarantee	3 years
Inner Pack Count	1
Quantity Per Box	32
EAN	3342540853874

---

Related product(s)	OK I'D® S AXIS 11 mm PAW CORDEX
--------------------	---------------------------------------------