



Product ID: RGH 2

Product Name: Two Point Harness

Accredited To: EN 361

Web Material: 45mm Water Repellent Polyester Webbing

Fittings: High Tensile Alloy

Weight: 1.15kgs

Features: Rear attachment point, Rip Stitch Indicators, Light Weight.

The RGH2 harness is the workhorse of the industry. The harness is fitted with a Rear Dee and a chest mounted Front Dee. This harness can be used similar to the RGH1 (see data sheet), but has the added feature of the Front Dee ring to extend the working capability of the harness. Utilizing the Front Dee, the harness can be fitted with a rope and grab system (RGA12) for vertical fall protection when an operative is making repeated ascents or similarly, when restraint /work-positioning is needed in either the vertical or horizontal plane. A variety of other devices can be used with the Front Dee ring, but please check for suitability. The harness is fully adjustable and is fitted with rip stitch indicators. The ring connection between the chest & the shoulder straps, ensure no stress loading when force is applied the Front Dee ring.

(For details of daily inspection procedures, see the info sheet)



TEL: +44 (0)1538 392616 FAX: +44 (0)1538 387350 Email: Sales@ridgegear.com

www.ridgegear.com

Head Office Ridgegear Ltd, Nelson Street, Leek, Staffordshire ST136BB United Kingdom

Part of the Unitex Group